Ev9617-21 4CB5-S Filter Cartridge		
<image/> <text></text>	4CB5-S Replacement Cartridge: EV9617-21	Water Purification Systems Image: System structure Image: System structure
INSTALLATION TIPS Never use saddle valve for connection Use 3/8" water line Install vertically with cartridge hanging down Allow 2-1/2" clearance below the cartridge for easy cartridge replacement Flush 4CB5-S cartridge by running water through filter for 5 minutes at full flow	OPERATION TIPS Change cartridges on a regular 6 month preventative maintenance program Change cartridges when capacity is reached or when pressure falls below 10 psi Service flow rate must not exceed 1.67 gpm Always flush the filter cartridge at time of installation and cartridge change	APPLICATION/SIZING Ideal for problem water areas For foodservice, vending machine and office coffee service applications Rated Capacity: 6,000 gallons (22,710 L)

4CB5-S Filter Cartridge

S P E C I F I C A T I O N S

Overall Dimensions: 14.5"H x 3.25"Diameter

Service Flow Rate: Maximum 1.67 gpm (6.3 Lpm)

Rated Capacity: 6,000 gallons

Pressure Requirements: 10 - 125 psi (0.7 - 8.6 bar), non-shock

Maximum Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

